

# Superior Mixing – Liquid, Gas and Powder

## IM 25 Rotary Jet Mixer

The patented IM 25 Rotary Jet Mixer (RJM) does not only mix fast, efficient and uniform but creates also the necessary process flexibility that makes it easy to switch to new product formulations with diverse viscosities, densities and volumes. Besides classic liquid to liquid mixing the RJM is excellent for gas and powder dispersion plus a superb tank cleaning machine.

**Applications**

Process and storage vessels between 10-1000 m<sup>3</sup> used in a wide range of industries such as: beer & beverage, food & ingredients, home & personal care, health care, biotech and chemical industry etc.

**Operation**

Secure that the mixer is positioned in the correct level and submerged into the liquid before round pumping or when adding any additional products from any up-stream pipe works.



**TECHNICAL DATA**

Lubricant: . . . . . Self-lubricating with the mixing/cleaning fluid  
 Connection: . . . . . Standard thread 2.5" BSP, female  
 Min. tank opening: . . . . . See dimension drawings

**Pressure**

Working pressure: . . . . . 2-12 bar  
 Recommended pressure during mixing: . . . . . 4-8 bar  
 Recommended pressure during CIP: . . . . . 5-10 bar

**PHYSICAL DATA**

**Materials**

Materials: . . . . . AISI 316L, AISI 316, SAF 2205, PEEK, PVDF, Carbon, Tefzel, Ceramics

**Weight:** . . . . . 13.2 kg

**Temperature**

Max. working temperature: . . . . . 95°C  
 Max. ambient temperature: . . . . . 140°C

**Benefits**

Using the IM 25 Rotary Jet Mixer makes it possible, at a modest investment, to perform fast and efficient mixing in a sanitary system. In traditional systems, using propeller mixers, a rotating shaft penetrates the tank wall and a mechanical seal and a gear box are installed. With the Rotary Jet Mixing technology the shaft, seal and gearbox are eliminated, and a more sanitary design is obtained. With the Rotary Jet Mixing technology good mixing is achieved without the use of baffles. The Rotary Jet Mixing technology can also be used for gas dispersion and for dispersion and dissolving of powder. The IM 25 can furthermore be used for efficient CIP when the tank is empty, saving liquid, chemicals and energy compared to a fixed spray ball CIP system.

