

Efficient Mixing and Agitation

Bottom mounted agitators Type ALB

Applications

Application	Typical examples
Maintain media homogeneous	Milk storage tanks, mixed product tanks, UHT storage tanks etc.
Mixing and Solutions (dissolves)	Fluid and fluid mixing, i.e. drinking yoghurt and fruit mix tanks, flavoured milk mix tanks, syrup mix tanks, etc.
Solid Dispersion	Powder + fluid mix tanks, etc.
Suspension	Fluids with particles, i.e. juice tanks
Heat transmission	Circulation of media in tanks with dimple jacket (cooling or heating)



TECHNICAL DATA

Motor

Motor size and speed as required for duty.
 As standard with IEC motor IP55, other types on request.
 As standard painted RAL5010.

Voltage and frequency

As standard for 3x380 to 420V, 50Hz - 3x440V to 480V, 60Hz.
 All motor voltages and frequencies are available.

Gears

Different gear types available according to configuration.
 As standard filled with normal synthetic or mineral oil, optional: Food approved oil. As standard painted RAL5010.

ATEX - option

Agitators can be delivered approved for use in an ATEX environment with declaration of conformity according to directive 94/9/EC.

Ordering

The following information is required to ensure correct sizing and configuration for ordering:

- Tank geometry
- Product properties
- Task of agitator
- Enquiry forms are available

PHYSICAL DATA

Materials

List the range of materials available for wetted parts:

Steel parts: AISI 316L (standard)
 AISI 304
 AISI 904L
 SAF 2205
 Other materials on request.

Seal rubber parts
 (o-rings or bellows): EPDM
 FPM/FEP (only for stationary o-rings)
 FPM
 Other materials on request.

Specific selection of materials will depend on the actual configuration selected.

Material certificate - option

3.1 Material certificates/FDA conformity statement according to 21 CFR177 on steel/elastomer parts in contact with media

Dimensions

Standard propeller diameter range: \varnothing 125 mm to 1900 mm.
 Specific dimensions on the drive unit and propeller(s) will depend on the actual configuration selected.